

Portability is key at every jobsite. The 8-gallon air compressor features an industrial electric motor, auto start/stop and flat-free tire that are perfect for transporting from one job to the next.

8-Gallon

Single Stage Electric

Compressor Pump:

- Splash lubricated
- Stainless-steel braided discharge hose
- Large canister intake filter
- Oil level sight indicator

Motor:

- Auto start/stop - continuous run optional
- Thermal overload motor protection

Frame:

- Powder coated 8-gallon twin tank receivers
- 3/16-inch base plate to reduce vibration
- 16-gauge powder coated two-piece belt guard
- Flat-free tire

Components:

- Regulator and two gauges for tank and outlet pressure
- Manual drain valves for proper maintenance
- 10-inch fly wheel
- Industrial-grade pressure switch

Limited Warranties:

- 1 year electric motor
- 2 year pump exchange
(see page 65 for information)

Certifications:

- CSA Certified



NEMA 5-15P,
15-amp plug



NEMA 5-20P,
20-amp plug

To see more online, scan here
or go to www.mitm.com



AM1-PE15-08M

MODEL NUMBER	CFM @ PSI	HORSEPOWER/MOTOR	COMPRESSOR	TANK SIZE	PLUG TYPE	DIMENSIONS (LxWxH)	SHIP WT.	NET WT.
AM1-PE15-08M	7.3 @ 90	1.5 HP, 120V, 13.2A	Single stage, cast iron	8-gallon	NEMA 5-15P	44.5x18.5x25in.	190 lb.	170 lb.
AM1-PE02-08M	9.2 @ 90	2.0 HP, 120V, 18.8A	Single stage, cast iron	8-gallon	NEMA 5-20P	44.5x18.5x25in.	203 lb.	183 lb.

Accessories & Options:

PART NUMBER	DESCRIPTION	FITS MODELS	PART NUMBER	DESCRIPTION	FITS MODELS
AW-6000-1002	Equipment cover	All models	AX-0003	Manual drain/regulator/metal bowl	All models
AX-0002	Auto drain/regulator/plastic bowl	All models	AX-0005	Dual control - continuous run & auto start/stop	All models