

Designed with both contractors and remodelers in mind, the 8-gallon two stage air compressor is perfect for jobsite tasks requiring a higher CFM and air capacity.

# 8-Gallon

## Two Stage Gasoline

**Compressor Pump:**

- Splash lubricated
- Stainless-steel braided discharge hose
- Large canister intake filter
- Oil level sight indicator

**Frame:**

- Powder coated 8-gallon twin tank receivers
- 3/16-inch base plate to reduce vibration
- 14-gauge powder coated two-piece belt guard
- Flat-free tires

**Components:**

- Regulator and two gauges for tank and outlet pressure
- Manual drain valves for proper maintenance
- 16 1/2-inch fly wheel
- Quality pilot valve unloader

**Limited Warranties:**

- 2 year pump exchange (see page 65 for information)
- 3 year Honda & Kohler engines
- 5 year Subaru engine

To see more online, scan here or go to [www.mitm.com](http://www.mitm.com)



AM2-PR09-08M

MODEL NUMBER	CFM @ PSI*	DISPLACEMENT/ENGINE	COMPRESSOR	TANK SIZE	ENGINE IDLE CONTROL	DIMENSIONS (LxWxH)	SHIP WT.	NET WT.
AM2-PH09-08M	17.2 @ 175	270cc Honda OHV	Two stage, cast iron	8-gallon	Pneumatic	44x26x31in.	330 lb.	260 lb.
AM2-PK95-08M	17.2 @ 175	277cc Kohler OHV	Two stage, cast iron	8-gallon	Cable throttle	44x26x31in.	330 lb.	260 lb.
AM2-PR09-08M	17.2 @ 175	265cc Subaru OHC	Two stage, cast iron	8-gallon	Pneumatic	44x26x31in.	330 lb.	260 lb.

\*Equipped with 150-PSI maximum rated regulator.

**Accessories & Options:**

PART NUMBER	DESCRIPTION	FITS MODELS	PART NUMBER	DESCRIPTION	FITS MODELS
AW-6000-1002	Equipment cover	All models	AX-0041	Electric start - battery and cables not included	AM2-PR09-08M
AX-0003	Manual drain/regulator/metal bowl	All models	IX-0055	Remote start/choke; 6-ft. wire extension for key switch; you will also need to order AX-0015	AM2-PH09-08M
AX-0015	Electric start - battery and cables not included	AM2-PH09-08M			